



CONSTRUCTION The Foam Filter consists of PPI 30 foam with aluminum expanded on both sides to assure maximum durability and internal loading capabilities. The media is enclosed in an aluminum frame, mitered and secured at one corner by rivets. The filter is designed for applications such as industrial, commercial, electronic equipment, office buildings, and air cleaners where a permanent filter is recommended. Maximum operating temperature on the Foam Filter is 250 degrees F. Available in both standard and special sizes.

MATERIAL Filtering element shall be processed from PPI 30 foam. Frame shall be made from sheet Aluminum 3003-H14, .025 thickness.

HIGHLIGHTS

- Uses PPI 30 foam
- Special design for maximum dust holding capacity
- Low resistance
- Washable and reusable
- Rust resistant

STANDARD SIZE FILTERS

Nominal Size (Actual size 1/2" under)	Part Number	Pack Ctn/ Lbs. Ctn
16 x 20 x 1/2	FF1620.5N	12 /11 lbs.
16 x 25 x 1/2	FF1625.5N	12 /13 lbs.
20 x 20 x 1/2	FF2020.5N	12 /13 lbs.
20 x 25 x 1/2	FF2025.5N	12 /15 lbs.
24 x 24 x 1/2	FF2424.5N	12 /17 lbs.
10 x 20 x 1	FF10201N	12 /17 lbs.
12 x 24 x 1	FF12241N	12 /19 lbs.
16 x 20 x 1	FF16201N	12 /19 lbs.
16 x 25 x 1	FF16251N	12 /21 lbs.
20 x 20 x 1	FF20201N	12 /21 lbs.
20 x 25 x 1	FF20251N	12 /23 lbs.
24 x 24 x 1	FF24241N	12 /26 lbs.